

SPK helix cable



Produced in high industrie quality, tested and guaranteed for 100.000 cycles in use under very harsh conditions. Achievement of high reset force and extension length.

Excerpt factor: 4

Due to the specially designed mixture of the casing the helix cable is resistant against: microbes, hydrolysis and almost every mineral oil. Further more the helix cable is UV-resistant and free of halogen.

Material PUR/PUR black, core colors according to DIN 47100: brown, white, green, yellow and black

Variable wire ends (see table), 40mm on both ends without sheathing and with core end sleeve (CES)

Name	Closed lenght	End 1	End 2	Order-no.
3-pin				
SPK 3x0,5mm ²	750	200	200	1.113 767
SPK 3x0,5mm ²	900	200	200	1.113 778
SPK 3x0,5mm ²	900	4000	350	1.114 006
SPK 3x0,5mm ²	1200	200	200	1.114 779
SPK 3x0,5mm ²	750	500	200	1.114 009
SPK 3x0,5mm ²	600	500	200	1.114 000
SPK 3x0,5mm ²	950	500	200	1.114 003
4-pin				
SPK 4x0,25mm ²	750	200	200	1.113 875
SPK 4x0,25mm ²	900	1000	400	1.113 770
SPK 4x0,25mm ²	1200	4000	400	1.113 771
5-pin				
SPK 5x0,25mm ²	500	1000	200	1.113 764
SPK 5x0,25mm ²	750	100	100	1.113 704
SPK 5x0,25mm ²	800	1500	200	1.113 762
SPK 5x0,25mm ²	900	200	300	1.113 739
SPK 5x0,25mm ²	900	2000	350	1.114 002
SPK 5x0,25mm ²	900	1500	200	1.114 005
SPK 5x0,25mm ²	1000	1000	1500	1.113 926
SPK 5x0,25mm ²	800	1600	300	1.113 921

